

Constant-Temperature Incubator

Features:

- * Intelligent temperature controller, based on microprocessor with PID parameters controlling function, and LCD display make temperature accurate and reliable.
- * The double door makes the temperature fluctuation small. The toughened-glass inner door is convenient to observe chamber condition without affecting chamber temperature.
- * The working chamber adopts 304 stainless steel and round angle structure, easy to clean.



BJPX-H30



BJPX-H50/80/160/270

Optional Accessories: * Independent temperature protector.

Technical Parameters:

Model	BJPX-H30	BJPX-H50	BJPX-H80	BJPX-H160	BJPX-H270
Capacity	30L	50L	80L	160L	270L
Temp. Range	RT+5~65°C				
Temp. Fluctuation	±0.3°C				
Time Setting	1~9999mins				
Alarm	Over-temperature alarm;audible and visual alarm.				
Shelves	2 pcs/adjustable			3 pcs/adjustable	
Consumption	200W	210W	280W	380W	570W
Power Supply	AC110/220V±10%, 50/60Hz				
Internal Size(mm)	320*300*315	350*350*410	400*400*500	500*500*650	600*600*750
External Size(mm)	650*470*510	510*520*800	580*570*890	680*670*1050	770*780*1150
Package Size(mm)	780*600*680	600*610*850	670*650*940	800*790*1200	890*890*1300
Gross Weight(kg)	45	55	57	90	130

Constant-Temperature Incubator

Features:

- * Large LED display, multiple groups of data to be displayed at a time; function of timing and over-temperature protection.
- * Two-layer toughened-glass observation window.



BJPX-H30/48/64/123II



BJPX-H230II

Technical Parameters:

Model	BJPX-H30II	BJPX-H48II	BJPX-H64II	BJPX-H123II	BJPX-H230II
Capacity	30L	45L	65L	125L	230L
Temp. Range	RT+5~80°C				
Temp. Fluctuation	±0.2°C				
Time Setting	1~9999mins				
Shelves	2 pcs/adjustable				
Consumption	150W	250W	500W	600W	700W
Power Supply	AC220V±10%, 50/60Hz				
Internal Size(mm)	310*310*310	350*350*350	400*360*450	500*450*550	600*500*750
External Size(mm)	460*510*695	500*550*735	550*550*840	636*680*915	730*670*1220
Package Size(mm)	550*570*765	620*585*800	640*640*905	730*720*1000	900*800*1350
Gross Weight(kg)	51	54	60	70	115